

KVM-Access-over-IP appliances comparison

© Copyright 2003 Rackit[®] Technology Corporation. All rights reserved.
Reproduction of this material in whole or in part for any purpose is prohibited.

| Feature | <u>IP-Reach M-Series</u> | <u>Smart IP Extender</u> | <u>Smart IP Link</u> | <u>SwitchView IP</u> |
|--|------------------------------|---|---|--|
| # of user paths | 1 or 2 | 1 | 1 | 1 |
| # of concurrent connections | 5 or 8 | 25 | 25 | 1 |
| TCP/IP connection | ✓ | ✓ | ✓ | ✓ |
| Network ports used | 5000 | 80 & 433 | 80 & 433 | 80, 433, 5900, & 12296 |
| Dial-up connection | Optional external modem | Built-in ISDN or optional external modem | Optional external modem | |
| Power management support | Hardware support | Hardware and software support | Hardware support | Hardware and software support |
| Integrated KVM switching | | ✓ | | |
| Remote client software | Web browser (Active-X based) | Web browser (Java based) | Web browser (Java based) | Web browser (Active-X based) |
| Client computer OS | Windows | Windows Linux MAC FreeBSD, BeOS | Windows Linux MAC FreeBSD, BeOS | Windows |
| Host computer OS | Windows | Windows Linux Novell 3.12-6 DOS FreeBSD, BeOS Unix | Windows Linux Novell 3.12-6 DOS FreeBSD, BeOS Unix | Windows Red Hat Linux 8 Novell NetWare 6 |
| Automatic video tuning & mouse synchronization | ✓ | ✓ | ✓ | ✓ |
| Manual video tuning & mouse synchronization | ✓ | ✓ | ✓ | |
| Single mouse mode | ✓ | ✓ | ✓ | |
| Max. resolution supported | 1280 x 1024 @ 60Hz | 1280 x 1024 @ 75Hz | 1280 x 1024 @ 75Hz | 1280 x 1024 @ 60Hz |
| SNMP enabled | ✓ | ✓ | | |
| LDAP compliant | | ✓ | | |
| Supports RADIUS authentication | ✓ | | | |