

MRS-1617

Rack-mount KVM console/switch

Monitor	
Display Area (inches)	• 13.516 (W) x 10.824 (H) • 17.0 inch diagonal
Resolution	1280 x 1024 pixels
Colors	True 16.7M Colors (6-bit + FRC algorithm)
Brightness	300 (cd/m2)
Contrast Ratio	450:1
Backlight Unit	4 replaceable CCFLs
Viewing Angle	• 60° ~ 60° (H) • 55° ~ 45° (V) (Typ.)
Screen Adjustment Controls	• Auto • Brightness • Pitch • Contrast • Color
Screen Type	Plug & Play
Video Input	Analog RGB (DDC2B)
Approvals	VESA DDC1 and DDC2B

Input/Output Devices	
Keyboard	PS/2, 104 keys
Touchpad	Synaptics Corp., PS/2
Speakers	Two 2-watt, stereo

Control Buttons & Indicators	
Power	On/Off power button
Speakers	On/Off Mute button

KVM Switch	
Ports	16, PS/2 compatible
Channel Selection	• On-Screen menu • Dedicated Buttons

Mechanical	
Dimensions - Fully open (Inches)	17¾W x 14¼H x 23¾D
Dimensions - Closed (Inches)	17¾W x 1¾H x 23¾D
Form Factor	1U, Rack-Mount
Depth Mounting Adjustment	23½ to 42 inches
Maximum pull (from front rail mount)	20-inches
Monitor base extension (from front rail mount)	7-inches
Maximum monitor tilt-back angle	135°

Connectors/Cables	
Keyboard Video Mouse Audio Connectors	16 all-in-one single connector (male) sockets
Power	AC inlet
Cables (included)	Sixteen 4-in-one single-connector KVM/Audio cables

Color	Black, fine-texture coating
Security	Cover lock, 2 keys
Power	• Built-in AC adaptor • 40 Watts • 100~240V universal
Operation Temperature	0° ~ 40° C (104° F)
EMI/SAFETY Agency approvals	FCC, UL, CE, CUL