

MRS-815

Rack-mount KVM console/switch

Monitor	
Display Area (inches)	12.125 (W) x 9.125 (H) 15.0 inch diagonal
Resolution	1024 x 768 pixels
Colors	True 16.7M Colors (24-bit color)
Brightness	250 (cd/m2)
Backlight Unit	2 replaceable CCFLs
Viewing Angle	60° ~ 60° (H) 55° ~ 45° (V) (Typ.)
Screen Adjustment Controls	- Auto - Brightness - Pitch - Contrast - Color
Screen Type	Plug & Play
Video Input	Analog RGB (DDC2B)
Approvals	VESA DDC1 and DDC2B

Input/Output Devices	
Keyboard	- Sunrex K9505 - PS/2, 88 keys
Touchpad	Synaptics Corp., PS/2
Speakers	Two 2-watt, stereo

Control Buttons & Indicators	
Power	On/Off power button
Speakers	On/Off Mute button

KVM Switch	
Ports	8, PS/2 compatible
Channel Selection	- On-Screen menu - Dedicated Buttons

Mechanical	
Dimensions - Fully open (Inches)	17¾W x 14¼H x 23¾D
Dimensions - Closed (Inches)	17¾W x 1¾H x 23¾D
Form Factor	1U, Rack-Mount
Depth Mounting Adjustment	23½ to 36 inches
Maximum pull (from front rail mount)	15-inches
Monitor base extension (from front rail mount)	3¼-inches
Maximum monitor tilt-back angle	130°

Connectors/Cables	
PS/2 Connectors	8 keyboard 6-pin Mini-DIN (female) sockets 8 mouse 6-pin Mini-DIN (female) sockets
Video Connectors	8 HD-15-pin VGA (male) sockets
Power	AC inlet
Audio-In Connectors	Eight 3.5 audio jacks
Cables (included)	- Eight 3-in-one KVM cables - Eight audio cables

Color	Black, fine-texture coating
Security	Cover lock, 2 keys
Power	- Built-in AC adaptor 40 Watts 90~264V universal
Operation Temperature	0° ~ 40° C (104° F)
EMI/SAFETY Agency approvals	FCC, UL, TUV, CE, CUL