

# Sylphit S-117

## Rack-mount KVM drawer

Monitor	
Display Area	17-inch diagonal
Resolution	1280 x 1024 pixels
Colors	True 16.7M colors
Brightness	250 nts
Contrast Ratio	350:1
Frequency	60 Hz
Bandwidth	200 MHz
Screen Adjustment Controls	<ul style="list-style-type: none"> <li>Brightness &amp; Contrast</li> <li>Image</li> <li>Color</li> <li>Language</li> <li>OSD</li> </ul>
Protection	<ul style="list-style-type: none"> <li>Anti-glare tempered glass</li> <li>Auto turn off</li> </ul>
Compliance	FCC; CE

Input Devices	
Keyboard	<ul style="list-style-type: none"> <li>Membrane, 105 keys</li> <li>PS/2, Windows</li> </ul>
Pointing Device	Touchpad, PS/2

Control Buttons & Indicators	
Power	On/Off button / Light
OSD Buttons	<ul style="list-style-type: none"> <li>Auto</li> <li>Up</li> <li>Menu</li> <li>Down</li> </ul>

Mechanical	
Form Factor	1U, Rack-Mount
Dimensions - Open	17½W x 14¼H x 21¾D
Depth Mounting Adjustment	19¾ to 39¼ inches
Maximum slide-out	17 inches
Maximum monitor base slide-out	3 inches
Maximum monitor tilt-back angle	105°
Security	<ul style="list-style-type: none"> <li>Unit closed – two locking thumb-screws</li> <li>Unit pulled out – self-locking rails</li> </ul>
Weight	36 lbs.
Shipping weight	47 lbs.
Shipping dimensions	29 x 24 x 8 inches

Connectors/Cables	
Console Port Connectors	<ul style="list-style-type: none"> <li>PS/2 keyboard, 6-pin Mini-DIN (female)</li> <li>PS/2 mouse, 6-pin Mini-DIN (female)</li> <li>VGA video, HD-15-pin (female)</li> </ul>
KVM 3-in-one Cable	<ul style="list-style-type: none"> <li>Male-to-male connectors</li> <li>6-feet</li> </ul>
Power	AC inlet

Color	Black, fine-texture coating
Power	<ul style="list-style-type: none"> <li>Built-in AC adaptor</li> <li>100~240V universal</li> </ul>
Operation Temperature	(32~104° F) 0~40° C
Operation Humidity	0 ~ 90% Non-Condensing