

Sylphit SK-815

Rack-mount KVM console/switch

| Monitor | |
|----------------------------|--|
| Display Area | 15-inch diagonal |
| Resolution | 1024 x 768 pixels |
| Colors | True 16.7M colors |
| Brightness | 250 nts |
| Contrast Ratio | 350:1 |
| Frequency | 60 Hz |
| Bandwidth | 200 MHz |
| Screen Adjustment Controls | <ul style="list-style-type: none"> Brightness & Contrast Image Color Language OSD |
| Protection | <ul style="list-style-type: none"> Anti-glare tempered glass Auto turn off |
| Compliance | FCC; CE |

| Input/Output Devices | |
|----------------------|---|
| Keyboard | <ul style="list-style-type: none"> Mechanical, 105 keys PS/2, Windows |
| Pointing Device | Touchpad, PS/2 |

| Control Buttons & Indicators | |
|------------------------------|--|
| Power | On/Off button / Light |
| KVM Switch | <ul style="list-style-type: none"> Channel push-buttons Channel indicators Bank LED |
| OSD Buttons | <ul style="list-style-type: none"> Auto Up Menu Down |

| KVM Switch | |
|-------------------|---|
| Ports | 8 PCs, 1 Daisy-Chain |
| Channel Selection | <ul style="list-style-type: none"> OSD Dedicated push-buttons Hot-Keys |

| Mechanical | |
|---------------------------------|--|
| Form Factor | 1U, Rack-Mount |
| Dimensions - Open | 17¾W x 14¼H x 23¼D |
| Depth Mounting Adjustment | 19¾ to 40½ inches |
| Maximum slide-out | 16½ inches |
| Maximum monitor base slide-out | 2¾ inches |
| Maximum monitor tilt-back angle | 105° |
| Security | <ul style="list-style-type: none"> Unit closed – two locking thumb-screws Unit pulled out – self-locking rails |
| Weight/Shipping Weight | 35 lbs. / 46 lbs. |
| Shipping dimensions | 30 x 24 x 8 inches |

| Connectors | |
|-----------------------------|---|
| Server Ports Connectors | <ul style="list-style-type: none"> 8 PS/2 keyboard 6-pin Mini-DIN (female) 8 PS/2 mouse, 6-pin Mini-DIN (female) 8 VGA video, HD-15-pin (female) |
| Daisy-Chain Port Connectors | <ul style="list-style-type: none"> 1, keyboard 6-pin Mini-DIN (female) 1, mouse 6-pin Mini-DIN (female) 1, HD-15-pin VGA (female) |
| Power | AC inlet |

| | |
|-----------------------|---|
| Color | Black, fine-texture coating |
| Power | <ul style="list-style-type: none"> Built-in AC adaptor 100~240V universal |
| Operation Temperature | (32~104° F) 0~40° C |
| Operation Humidity | 0 ~ 90% Non-Condensing |