

Sylphit SKW-817

Rack-mount KVM console/switch, wide-screen

RACKit[®]
Technology Corporation
Product Specifications

Monitor	
Display Area	17-inch diagonal (16:9)
Resolution	1280 x 768 pixels
Colors	True 16.2M colors
Brightness	450 nits
Contrast Ratio	800:1
Frequency	60 Hz
Bandwidth	200 MHz
Screen Adjustment Controls	<ul style="list-style-type: none">Brightness & ContrastImage PositioningColorLanguageOSD
Protection	<ul style="list-style-type: none">Anti-glare tempered glassAuto turn off
Compliance	FCC; CE

Input Devices	
Keyboard	<ul style="list-style-type: none">Membrane, 105 keysPS/2, Windows
Pointing Device	Touchpad, PS/2

Control Buttons & Indicators	
Monitor	On/Off Button & Light
KVM Switch	<ul style="list-style-type: none">Channel push-buttonsChannel indicatorsBank LED
OSD Buttons	<ul style="list-style-type: none">AutoUpMenuDown

KVM Switch	
Ports	8 PCs, 1 Daisy-Chain
Channel Selection	<ul style="list-style-type: none">OSDDedicated push-buttonsHot-Keys

Mechanical	
Form Factor	1U, Rack-Mount
Dimensions - Open	17½W x 12H x 20D
Depth Mounting Adjustment	20 to 33 inches
Maximum slide-out	13¾ inches
Maximum monitor base slide-out	2¾ inches
Maximum monitor tilt-back angle	105°
Security	<ul style="list-style-type: none">Unit closed – two locking thumb-screwsUnit pulled out – self-locking rails
Weight/Shipping Weight	26 lbs. / 43 lbs.
Shipping dimensions	28 x 24 x 8 inches

Cables/Connectors	
Cables (included)	8 "Combo" 3-in-one, single-sheath cables
Server Ports Connectors	8 "Combo" connectors, HDB-15-pin (female)
Daisy-Chain Port Connectors	<ul style="list-style-type: none">1, keyboard 6-pin Mini-DIN (female)1, mouse 6-pin Mini-DIN (female)1, video HD-15-pin VGA (female)
Power	DC jack (12V, 4A)

Color	Black, fine-texture coating
Power	<ul style="list-style-type: none">External AC adaptor100~240V, 50/60 Hz universal, 2A
Operation Temperature	(32~122° F) 0~50° C
Operation Humidity	0 ~ 90% Non-Condensing