

Sylphit USK-817

Rack-mount KVM USB console/switch

Monitor	
Display Area	17-inch diagonal
Resolution	1280 x 1024 pixels
Colors	True 16.7M colors
Brightness	280 nts
Contrast Ratio	400:1
Frequency	60 Hz
Bandwidth	200 MHz
Screen Adjustment Controls	<ul style="list-style-type: none">Brightness & ContrastImageColorLanguageOSD
Protection	<ul style="list-style-type: none">Anti-glare tempered glassAuto turn off
Compliance	FCC; CE

Input/Output Devices	
Keyboard	<ul style="list-style-type: none">Mechanical, 105 keysUSB, Windows
Pointing Device	Touchpad, USB

Control Buttons & Indicators	
Power	On/Off button / Light
KVM Switch	<ul style="list-style-type: none">Channel push-buttonsChannel indicatorsBank LED
OSD Buttons	<ul style="list-style-type: none">AutoUpMenuDown

KVM Switch	
Ports	8 PCs, 1 Daisy-Chain
Channel Selection	<ul style="list-style-type: none">OSDDedicated push-buttonsHot-Keys

Mechanical	
Form Factor	1U, Rack-Mount
Dimensions - Open	17½W x 14¼H x 24⅝D
Depth Mounting Adjustment	19¾ to 40 inches
Maximum slide-out	17 inches
Maximum monitor base slide-out	3 inches
Maximum monitor tilt-back angle	110°
Security	<ul style="list-style-type: none">Unit closed – two locking thumb-screwsUnit pulled out – self-locking rails
Weight/Shipping Weight	34 lbs. / 45 lbs.
Shipping dimensions	30 x 24 x 8 inches

Connectors	
Server Ports Connectors	Eight (8) all-in-one HD15 (female)
Daisy-Chain Port Connector	One (1) all-in-one HD15 (female)
External Local Console Connectors	<ul style="list-style-type: none">Dual USB connectorHD15 (female) VGA connector
Power	AC inlet

Environmental	
Color	Black, fine-texture coating
Power	<ul style="list-style-type: none">Built-in AC adaptor100~240V Auto-Switch
Operation Temperature	(32~122° F) 0~50° C
Operation Humidity	0 ~ 90% Non-Condensing