

Sylphit SK-1617

Rack-mount KVM console/switch

Monitor	
Display Area	17-inch diagonal
Resolution	1280 x 1024 pixels
Colors	True 16.7M colors
Brightness	250 nits
Contrast Ratio	350:1
Frequency	60 Hz
Bandwidth	200 MHz
Screen Adjustment Controls	<ul style="list-style-type: none"> Brightness & Contrast Image Color Language OSD
Protection	<ul style="list-style-type: none"> Anti-glare tempered glass Auto turn off
Compliance	FCC; CE

Input Devices	
Keyboard	<ul style="list-style-type: none"> Membrane, 105 keys PS/2, Windows
Pointing Device	Touchpad, PS/2

Control Buttons & Indicators	
Power	On/Off button / Light
KVM Switch	<ul style="list-style-type: none"> Channel push-buttons Channel indicators Bank LED
OSD Buttons	<ul style="list-style-type: none"> Auto Menu Up Down

KVM Switch	
Ports	16 PCs, 1 Daisy-Chain
Channel Selection	<ul style="list-style-type: none"> OSD Dedicated push-buttons Hot-Keys

Mechanical	
Form Factor	1U, Rack-Mount
Dimensions - Open	17½W x 14¼H x 24¼D
Depth Mounting Adjustment	19¾ to 41½ inches
Maximum slide-out	17 inches
Maximum monitor base slide-out	3 inches
Maximum monitor tilt-back angle	105°
Security	<ul style="list-style-type: none"> Unit closed – two locking thumb-screws Unit pulled out – self-locking rails
Weight/Shipping Weight	39 lbs. / 64 lbs.
Shipping dimensions	31½ x 24 x 9½ inches

Cables/Connectors	
Cables (included)	16 "Combo" 3-in-one, single-sheath cables
Server Ports Connectors	16 "Combo" connectors, HDB-15-pin (female)
Daisy-Chain Port Connectors	<ul style="list-style-type: none"> 1, keyboard 6-pin Mini-DIN (female) 1, mouse 6-pin Mini-DIN (female) 1, video HD-15-pin VGA (female)
Power	AC inlet

Color	Black, fine-texture coating
Power	<ul style="list-style-type: none"> Built-in AC adaptor 100~240V universal
Operation Temperature	(32~104° F) 0~40° C
Operation Humidity	0 ~ 90% Non-Condensing